

DALI DIMMABLE DRIVERS

CC TUNABLE WHITE SERIES DT8



DESCRIPTION

- Two Channel Output, Output Current Level Selectable By Dip S.w.
- Meet Dali Protocol IEC 62386-209
- Efficiency 80-88%
- High Power PF > 0.95
- Support Touch Dim Function
- Built -in Active Pfc Function
- Dimming Effect Smooth, No Flicker
- Protection: Short Circuit, Over Load, Over Temperature
- Suitable For Indoor Led Lighting Application such as Down Light, Panel Light and so on

PART NO	OUTPUT VOLTAGE (Vdc)	Output Current	Output Wattage (W)
EUP12D-2HMC-0	9 - 42	120 / 150 / 180 / 200mA 240 / 270 / 300 / 350mA	12
EUP20D-2HMC-0	9 - 42	350 / 400 / 450 / 500 / 550 600 / 650 / 700mA	20
EUP40D-2HMC-0	9 - 42	500 / 600 / 700 / 800mA	34
EUP50D-2HMC-0	9 - 45	900 / 1050 / 1200 / 1400mA	50



CC TUNABLE WHITE SERIES DT8

DESCRIPTION

- Two Channel Of Constant Voltage Output
- Meet Dali Protocol IEC 62386 DT8
- Efficiency 90-92%
- High Power PF > 0.95-0.98
- High Input Voltage Of 120vac - 270vac
- Dimming Effect Smooth, No Flicker
- Overload Protection, Over Voltage Protection, Short Circuit Protection
- IP20, Suitable for Indoor Led, Lighting Application

PART NO	OUTPUT VOLTAGE (Vdc)	Output Current	Output Wattage (W)
LCP75D-2W12V	12V	6.25mA	75
LCP75D-2W24V	24V	3.125mA	75
LCP150D-2W12V	12V	12.5mA	150
LCP150D-2W24V	24V	6.25mA	150



For More Information : www.euchips.com

OEM For Green World Technology

DALI DIMMABLE DRIVERS

DALI 2.0 CONSTANT CURRENT SERIES



DESCRIPTION

- Single channel output, Output current level selectable by dip S.W.
- Meet Dali protocol IEC 62386-207
- Efficiency 80-88%
- High Power PF > 0.95
- Support Touch Dim (Push Dim) function
- Built - in active pfc function
- Dimming effect smooth, No flicker
- Protection : Short Circuit, Over Load, No Load
- Suitable for indoor led lighting application such as Down Light, Spot Light and so on

PART NO	OUTPUT VOLTAGE (Vdc)	Output Current	Output Wattage (W)
EUP10D-1HMC-0	9 - 40	120 / 180 / 240 / 300mA	10
EUP12D-1HMC-0	9 - 40	200 / 250 / 300 / 350mA	12
EUP20D-1HMC-0	9 - 40	350 / 500 / 550 / 700mA	20
EUP30D-1HMC-0	9 - 45	550 / 600 / 650 / 700 / 750 / 800 / 850 / 900mA	30
EUP40D-1HMC-0	9 - 45	850 / 900 / 950 / 1000 / 1050 / 1100 / 1200mA	40



DALI CONSTANT VOLTAGE SERIES

DESCRIPTION

- Single Channel constant voltage output, 1A to 17A
- Meet Dali protocol IEC 62386
- Efficiency 85-90%
- High Power PF > 0.95
- Support Touch Dim Function
- Dimming Effect Smooth, No Flicker
- Over Temperature Protection
- Short circuit protection, Overload protection
- IP20, Suitable for Indoor Led, Lighting application



PART NO	OUTPUT VOLTAGE (Vdc)	Output Current	Output Wattage (W)
EUP24D-1H24V-0	24	1A	24
EUP75D-1H12V-0	12	6.2A	75
EUP75D-1H24V-0	24	3.1A	75
EUP200AD-1H12V-0	12	17A	200
EUP200AD-1H24V-0	24	8.3A	200
LCP75AD-1H12V-0	12	6.2A	75
LCP75AD-1H24V-0	24	3.1A	75
LCP120AD-1H12V-0	12	10A	120
LCP150AD-1H24V-0	24	6.25A	150



For More Information : www.euchips.com

OEM For Green World Technology